

中央印製廠 Central Engraving And Printing Plant	聚氯化鋁 Poly Aluminum Chloride		編號	4101
			生效日期	1050314
檢驗項目 Item	單位 Unit	規格 Specification	備註 Remarks	
氧化鋁 Al ₂ O ₃	%	10.0-11.0	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	
pH 值 pH Value		3.5-5.0	1W/V%水溶液 參考 CNS(同上) 1% aqueous solution	
比重 Specific Gravity		>1.19	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	
外觀 Physical Aspect		淡棕色透明液體 (無色或稍帶黃色) Light brown transparent liquid (Achromatic or light yellow)	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	
鐵(Fe)	ppm	<100	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	
錳(Mn)	ppm	<25	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	
鉛(Pb)	ppm	<10	參考 CNS 12537 K1278 Ref.CNS 12537 K1278	

1.使用化學藥品罐車直接注入本廠儲存槽中。

Pour into our plant's storage tanks by chemicals tanker trucks.

2.視需要用量通知逐次送貨。

Deliver the goods informed according to the amount of need.

3.交貨廠商須提供製造廠最新之產品技術資料(含功能、特性)、符合勞動部規定新版 16 項之中文正體字安全資料表 (GHS-SDS)、當批次出廠檢驗報告，供檢測單位及使用單位參考。

The supplier should provide the latest manufacturer's technical information of the product (including functions and characteristics), the safety data sheet (GHS-SDS) which must contain 16 information items of the latest Traditional Chinese version regulated by ministry of labor affairs, one copy of inspection certificate of each lot for the reference of the inspection and using departments.